



DISPOSABLE EARPLUGS

SOFT COMFORTABLE FIT

Softies are made of extra-soft, extra-light foam. Their tapered design shape fits easily in the ear canal. Softies seal snugly without uncomfortable pressure. Their outer surface is smooth, so it doesn't irritate the ear canal. 100% PVC-Free.

EASY COMPLIANCE CHECKS

The bright radiant orange color of the Softies make compliance checks easy.

HIGHEST INDEPENDENTLY TESTED NRR 33

Softies offer the highest independently tested NRR 33 rating available, making them suitable for most noisy environments. They are independently tested by Michaels & Associates, Inc. and are tested to ANSI S3.19-1974. Not only are they comfortable, but they also provide serious protection.

FEATURES

- Highest independently tested NRR 33 available.
- Radiant orange color for easy compliance checks.
- Extra-soft, low-pressure foam for comfort and fit.
- Tapered shape for easy insertion and removal.
- Shaped to fit even very small ear canals.
- Non-irritating smooth surface.
- Independently tested to ANSI S3.19-1974.
- 100% PVC-Free.



Softies 6683 TouchFree EcoStation

DISPOSABLE EARPLUGS

PART #	DESCRIPTION	DISPLAY QUANTITY	CASE QUANTITY
6600	Uncorded earplugs	200 Pairs / Box	10 Boxes / Case
6650	Corded earplugs	100 Pairs / Box	20 Boxes / Case
6683	Earplug Canister	40 Pairs / Canister	36 Canisters / Case
6701	EcoStation® Starter Pack	500 Pairs / Dispenser	4 Dispensers / Case
6702	EcoStation® Refill	500 Pairs / Dispenser	4 Dispensers / Case
6831	TouchFree EcoStation®	500 Pairs / Dispenser	4 Dispensers / Case
6931	EcoStation® Copper	500 Pairs / Dispenser	4 Dispensers / Case



Softies 6683 Earplug Canister

More info at moldex.com/product/earplug-canisters

ATTENUATION DATA / DATOS DE ATENUACIÓN / DONNÉES D'ATTÉNUATION

Tested According to ANSI Specs S3.19-1974 by Michael & Assoc., State College, PA.

Probado de acuerdo a las especificaciones ANSI S3.19-1974 Michael & Assoc., State College, PA.

Tests Conformes aux Spécs. ANSI S3.19-1974 Michael & Assoc., State College, PA.

Frequency (Hz) Frecuencia (Hz) Fréquence (Hz)	125	250	500	1000	2000	3150	4000	6300	8000		
Mean Attenuation (dB) Datos de Atenuación (dB) Atténuation Moyenne (dB)	42.3	43.7	46.6	40.9	38.6	44.7	46.9	49.3	48.3	NRR 33	CSA AL
Standard Deviation (dB) Desviación Estándar (dB) Écart Standard (dB)	5.0	6.0	5.8	4.2	2.8	3.2	3.3	4.2	3.6		

WARNING TO USER

- Use these laboratory derived attenuation data for comparison purposes only. The amount of protection afforded in field use often is significantly lower depending upon how the protectors are fitted and worn.
- Failure to obtain a proper fit will reduce effectiveness of hearing protectors and could result in hearing loss or injury.
- Over protection can be dangerous. The wearer must be able to hear warning signals.
- Wearers with hearing loss should exercise extreme caution.
- It is the employer's responsibility to ensure that the type of hearing protector and its rating is appropriate for the user in their particular workplace.
- Failure to follow all instructions and warnings could result in increased risk of hearing loss, serious injury or death.
- Use caution when working around machinery or any other equipment to ensure neck cord does not become caught or entangled.
- Softies foam earplugs must only be used as part of a hearing conservation program that complies with applicable local safety and health regulations.

MOLDEX TECHNICAL ASSISTANCE

Moldex provides all of the technical assistance required to set up a hearing protection program. For more information call +1 (800) 421-0668 or +1 (310) 837-6500 ext. 512, email: tech@moldex.com or visit www.moldex.com.

Keep earplugs away from infants and small children as they may get caught in the windpipe and create a choking hazard.



DISTRIBUTED BY:

MOLDEX-METRIC, INC.

10111 Jefferson Blvd.

Culver City, CA 90232

TEL: +1 (800) 421-0668 or +1 (310) 837-6500

FAX: +1 (310) 837-9563

Email: sales@moldex.com | www.moldex.com

U.S. & CANADA CUSTOMER SERVICE

TEL: +1 (800) 421-0668, Ext. 550

